



# POLYSTAB SS

## DESCRIPTION

POLYSTAB SS is an additive for concrete with a high cement content, particularly suitable for use during the winter months, which stabilizes, accelerates the setting time, facilitates the laying of the concrete even if with a reduced water content and allows the use of aggregates containing clay, silt or sand.

## APPLICATION

POLYSTAB SS can be used on any type of concrete, in particular those with a high cement content (other 150 kg / m<sup>3</sup>) such as car parks, maneuvering areas, cycle paths, draining concrete. It also allows the creation of concrete conglomerates for cycle paths or stabilized roads directly on site, mixing soil, aggregates and cement directly in place.

## DIRECTIONS OF USE

POLYSTAB SS is liquid and is added directly into the water used to mix the concrete, alternatively it can be added in the mixing phase when adding water.

## DOSAGE

The dosage of POLYSTAB SS normally varies from 1% to 4% of the weight of the cement, higher dosages are possible in the case of installation in particularly cold climates.

## STORAGE

POLYSTAB SS can be stored for 24 months in its original closed packaging, at a temperature between 5 ° C and 30 ° C. Depending on the storage temperature, the product can vary viscosity, however its characteristics are not compromised.

## SAFETY

For more information on classification, protective measures and measures in case of fire, please refer to the product safety data sheet, available on request.

## WARNINGS

The advice on the methods of use correspond to the current state of our knowledge and do not imply the assumption of any guarantee and / or responsibility on the final result of the work. Therefore, they do not exempt the customer from the responsibility of verifying the suitability of the products for the intended use and purposes through preventive tests.